

WOLF TRACTOFLUID 170 BM

29/02/2024
23121

Special oil, intended for automatic transmissions, hydraulic systems, wet brakes, convertors for tractors, forklifts and different off-highway equipment. Remark : When the manufacturer prescribes only one oil for the lubrication of all parts, the engine included, he refers to a S.T.O.U. oil.

APPLICATIONS

This oil meets the requirements of Volvo BM, and can be used in transmissions, lifters, rear axles and wet brakes of agricultural tractors and off-highway equipment as well as moving hydraulic systems (cranes, junction box, power steering).

FEATURES

Anti-wear and oxidation stability: superior protection of critical parts
Cold start: excellent fluidity at low temperature

SPECIFICATIONS

API	GL-4	ZF	approval TE-ML 03E
ALLISON	C4	ZF	approval TE-ML 05F
CASE	MAT 3505	ZF	approval TE-ML 06K
CASE	MAT 3510	ZF	approval TE-ML 17E
CASE	MAT 3525	ZF	approval TE-ML 21F
CASE	MAT 3526	ZF	TE-ML 06B
CASE	MAT 3540	ZF	TE-ML 06D
CASE	MS1206	ZF	TE-ML 06E
CASE	MS1207	ZF	TE-ML 06F
CASE	MS1209	ZF	TE-ML 06H
CASE	MS1210	ZF	TE-ML 06M
CATERPILLAR	MTO	ZF	TE-ML 06N
CATERPILLAR	TO-2	ZF	TE-ML 06P
FORD	ESN-M2C-134 C/D	ZF	TE-ML 06R
FORD	ESN-M2C-86 A/B	ZF	TE-ML 06S
FORD	ESN-M2C-86 C	ZF	TE-ML 06T
FORD	FNHA-2-C-201.00		
JD	J20 C/D		
KOMATSU	KES 07.866		
KUBOTA	UDT		
MF	M 1127/M 1129A		
MF	M 1135		
MF	M 1143		
MF	M 1145		
NH	NH 410B		
VALTRA	G2-08		
VALTRA	G2-B10		
VOLVO	approval 97303/WB101		

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com



TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.875
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	68.3
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	10.9
Viscosity index	ASTM D2270		150
B.N. (HClO ₄ method)	ASTM D2896	mg KOH/g	7.6
Pour point	ASTM D6892	°C	-39
Flash Point COC	ASTM D92	°C	212
Brookfield viscosity at -18°C	ASTM D2983	mPa.s	2000

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

