

WOLF GUARDTECH

SAE 40 SF/CD

11/08/2023
184

Monograde engine oil for the lubrication of gasoline and diesel engines of passenger cars, with or without turbo. This oil is characterized by a combination of good detergent and dispersant properties, together with a low ash content.

APPLICATIONS

This oil is suitable for the lubrication of gasoline and diesel engines from 1980 to 1989.

FEATURES

Total engine protection: engine protection and cleanliness

PERFORMANCE

API	SF/CD	MB	226.0
MIL	L-46152 B		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.895
Kinematic viscosity at 40°C	ASTM D445	mm²/s	145
Kinematic viscosity at 100°C	ASTM D445	mm²/s	14.1
Viscosity index	ASTM D2270		94
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	5.6
Pour point	ASTM D6892	°C	-33
Flash Point COC	ASTM D92	°C	250

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com

