

MULTIPURPOSE GREASE 3

12/08/2023
9103

This is a lubricating grease for general applications, where no specific requirements are made. This grease has a good oxidation stability, so that it can ensure long-lasting lubrication. It is water-resistant and has good temperature characteristics. Therefore it can be used at high temperatures and it stays pumpable at low temperatures making it suitable for bearing lubrication.

APPLICATIONS

This grease can be used in both industrial and automotive applications. It is suitable for a wide range of plain and rolling bearings. Temperature range: -30°C to +120°C, Max. +130°C

FEATURES

-: Good mechanical stability

PERFORMANCE

| | | | |
|-----|--------|-----|----------|
| DIN | 51502 | ISO | 6743 |
| DIN | K3K-30 | ISO | L-XCCFA3 |

TYPICAL CHARACTERISTICS

| Test | Method | Unit | Average results |
|---------------------------------|---------------------------|--------|-----------------|
| Texture | Visual | | Smooth |
| Colour | VISUAL | | Light Brown |
| NLGI Classification | ASTM D217 | | 3 |
| Worked Penetration (60 strokes) | ISO 2137 | 0.1 mm | 235 |
| Dropping point | ISO 2176/IP 396 | °C | 190 |
| Four Ball Weld Load | ASTM D2596/ DIN51350:4 | N | 2000 |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolfoil.com

WOLFOIL
CORPORATION