

# CHAMPION FLUSHING OIL

*This is a low viscosity mineral oil with good flushing and cleaning properties.*

## APPLICATIONS

*It is primarily used for flushing the oil sump and lubrication systems of internal combustion engines. It can also be used for flushing transmissions and gear boxes, to remove dirt and wear particles.*

## FEATURES

*Cleaning properties: very good detergent and dispersant characteristics*

## PERFORMANCE

ISO 6743/10

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.900
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	20.8
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	3.8
Viscosity index	ASTM D2270		45
Pour point	ASTM D6892	°C	-33
Anilin point	ASTM D611	°C	78
Flash Point COC	ASTM D92	°C	170

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

[www.championlubes.com](http://www.championlubes.com)

