

WOLF OFFICIALTECH 5W-30 MS-SFE

07/04/2025
65663

A low SAPS ACEA C3 passenger car engine oil focused on the most recent Stellantis specification FPW9.55535/03 and on the PSA specifications B71 2290 and B71 2297 (for hot climates). Also suitable for diesel and gasoline engines from other car manufacturers which require an ACEA C3 SAE 5W-30 oil.

APPLICATIONS

Developed for a wide range of passenger cars, SUVs and light vans. It is designed for modern high efficiency gasoline, diesel and hybrid cars from Stellantis (PSA, Opel, Vauxhall), MB and GM, as well as for Asian vehicles that specifically require a SAE 5W-30 oil specification.

FEATURES

Aftertreatment protection: full aftertreatment device protection.

Cold start: excellent fluidity at low temperature.

Fuel economy: superior fuel economy and CO2 reduction.

SPECIFICATIONS

ACEA	C3	MB	229.52
API	SN Plus	PSA	B71 2290
GM	dexos2™	PSA	B71 2297
MB	229.31	STELLANTIS	FPW9.55535/03
MB	229.51		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.847
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	66.1
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	11.5
Viscosity index	ASTM D2270		170
Pour point	ASTM D6892	°C	-42
Flash Point COC	ASTM D92	°C	254

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

