

# WOLF OFFICIALTECH 0W30 MS-FFE

14/04/2025  
65618

This is a full synthetic lubricant based on carefully selected base oils, mandatory for the EURO 6 TDCI Duratorq engines of the most recent Ford models (2014 - ...) with exhaust after treatment and turbocharger. The high-tech VI-improver provides high stability to ensure long oil drain intervals. It also addresses the use of biofuels, has special elastomer compatibility and anti chain wear characteristics.

## APPLICATIONS

This product is developed for mandatory use in the newest EURO 6 TDCI Duratorq Ford engines. This product is also usable for other passenger car engines requiring a 0W30 viscosity grade and the ACEA C2 performance, thus providing a multi vehicle oil application. Optimum formulation for today's car engines with exceptional fuel economy and extended service intervals.

## FEATURES

Total engine protection: performance in keeping the engine clean  
Fuel economy: superior fuel economy and CO2 reduction  
Cold start: excellent fluidity at low temperature

## SPECIFICATIONS

ACEA	C2	HONDA	SFU
API	SN	JAGUAR-LAND ROVER	approval STJLR.03.5007
ILSAC	GF-5	MITSUBISHI	SFU
FIAT	9.55535-DS1	SUZUKI	SFU
FIAT	9.55535-GS1	TOYOTA	SFU
FORD	WSS-M2C950-A	VW	530 35

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.844
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	48.9
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	9.6
Viscosity index	ASTM D2270		187
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	8.0
Pour point	ASTM D6892	°C	-42
Sulfated Ash	ASTM D874	Mass %	0.79
Flash Point COC	ASTM D92	°C	210
CCS viscosity at -35°C	ASTM D5293	mPa.s	5600

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolf lubes.com](http://www.wolf lubes.com)

