

CHAMPION OEM SPECIFIC

80W-90 LS GL 5 ZF-N

This high performance ZF 05N/21N gear oil is an advanced all-round lubricant, which is balanced to lubricate a wide range of axles including the ones equipped with limited slip (LS) and hypoid gears. Its formula offers outstanding extreme-pressure resistance, which is proven by its typical phosphorus content of 2000 ppm.

APPLICATIONS

This officially approved ZF 05N/21N formula can be used to service axles with or without limited slip differential or multi-disc differential. Furthermore, it suits the needs of different axles and differentials with or without hypoid drive. This multi-use gear oil can be used within dumpers, wheel loaders, mobile excavators, tractor axles, planetary final drives and even in certain rail vehicles & bus transmission systems with multi-disc self-locking differentials. This innovative lubricant allows you to make fleet maintenance more efficient by reducing the amount of different fluids you need.

FEATURES

Phosphorus content of 2000 ppm: advanced extreme-pressure resistance

Broad applicability: easier fleet maintenance with this all-round product

Improved component cleanliness: prevent slip disks and gears from experiencing additional wear

SPECIFICATIONS

API	GL-5
API	MT-1
ARVIN MERITOR	AXLES
FORD	WSS-M2C197-A+M2C118-A
GM	1942382
GM	1942387
GM	9121965
JD	J11 F
JD	JDM J11F
MACK	GO-J
SDFG	OP1705LS
VOLVO	97310
VOLVO	STD 1273,21 (97321)
ZF	approval TE-ML 05N
ZF	approval TE-ML 21N
ZF	TE-ML 05C
ZF	TE-ML 07A
ZF	TE-ML 08
ZF	TE-ML 12C
ZF	TE-ML 16E
ZF	TE-ML 21C

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

www.championlubes.com





TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.880
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	131
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	14.2
Viscosity index	ASTM D2270		115
A.N. [Colorimetric]	ASTM D974	mg KOH/g	1.20
Pour point	ASTM D6892	°C	-36
Phosphorus	ASTM D5185	mg/kg	2000

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

