

# WOLF AROW ISO 15

11/08/2023  
4002

A mineral oil, specifically designed to meet the requirements of most important manufacturers of hydraulic equipment. It contains anti-wear, anti-oxidant, anti-corrosion and anti-foam additives.

## APPLICATIONS

This oil is specifically designed to satisfy the requirements of the manufacturers of hydraulic systems where the highest demands are made concerning high pressure, temperatures or speeds. It is recommended for the hydraulic systems of the following types : Vickers, Gerotor, Gresen, HPM, Denison, Cessna, Hydreco and Worthington. It is also suitable for the lubrication of workshop equipment, reducing gears, bearings, compressed air systems and air screw compressors.

## FEATURES

Anti-wear and oxidation stability: superior protection

Anti-foam properties: excellent anti-foam properties

Temperature stability: adequate viscosity stability

## PERFORMANCE

AFNOR	NF E 48-603 HM	ISO	6743-4, HM
AFNOR	NF E 48-690	DENISON	HF-2
AFNOR	NF E 48-691	EATON VICKERS	I-286-S
DIN	51524 Part 2	EATON VICKERS	M-2950-S
ISO	11158, HM		

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.846
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	14.8
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	3.5
Viscosity index	ASTM D2270		115
Pour point	ASTM D6892	°C	-30
Flash Point COC	ASTM D92	°C	169

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolf lubes.com](http://www.wolf lubes.com)

