WOLF MULTIPURPOSE GREASE 2

11/08/2023 9100

This is a lubricating grease for general applications, where no specific requirements are made. This lithium based grease has a good oxidation stability, so that it can ensure long-lasting lubrication. It is water-resistant and has good temperature characteristics. Therefore it can be used at high temperatures and it stays pumpable at low temperatures making it suitable for bearing lubrication.

APPLICATIONS

This grease can be used in both industrial and automotive applications. It is suitable for a wide range of plain and rolling bearings. Temperature range: -30°C to +120°C, Max. +130°C

FEATURES

For industrial and automotive applications: For industrial and automotive applications

PERFORMANCE

DIN	51502	ISO	6743
DIN	K2K-30	ISO	L-XCCEA2

TYPICAL CHARACTERISTICS

Method	Unit	Average results
Visual		Smooth
VISUAL		Yellowish Brown
ASTM D217		2
ISO 2137	0.1 mm	265-295
ISO 2176/IP 396	°C	190
ASTM D2596/ DIN51350:4	N	2000
	Visual VISUAL ASTM D217 ISO 2137 ISO 2176/IP 396 ASTM D2596/	Visual VISUAL ASTM D217 ISO 2137

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

