

WOLF AROW ISO 10

A mineral oil, specifically designed to meet the requirements of the most important manufacturers of hydraulic equipment. It contains anti-wear, anti-oxidant, anti-corrosion and anti-foam additives.

ZASTOSOWANIA

This oil is specifically designed to satisfy the requirements of the manufacturers of hydraulic systems where the highest demands are made concerning high pressure, temperatures or speeds. It is recommended for the hydraulic systems of the following types : Vickers, Gerotor, Gresen, HPM, Denison, Cessna, Hydreco and Worthington. It is also suitable for the lubrication of workshop equipment, reducing gears, bearings, compressed air systems and air screw compressors.

CECHY

Anti-wear and oxidation stability: superior protection

Anti-foam properties: excellent anti-foam properties

Temperature stability: adequate viscosity stability

SPECYFIKACJA

AFNOR	NF E 48-603 HM	ISO	6743-4, HM
AFNOR	NF E 48-690	DENISON	HF-2
AFNOR	NF E 48-691	EATON VICKERS	I-286-S
DIN	51524 Part 2	EATON VICKERS	M-2950-S
ISO	11158, HM		

TYPOWE CECHY

Test	Metoda	Jednostka	Średni wynik
Gęstość w temp. 15°C	ASTM D4052	g/ml	0.836
Lepkość kinematyczna przy temp. 40°C	ASTM D445	mm ² /s	10.8
Lepkość kinematyczna w temp. 100°C	ASTM D445	mm ² /s	2.82
Indeks lepkości	ASTM D2270		119
Temperatura krzepnięcia	ASTM D6892	°C	-33
Temperatura zapłonu metodą Cleveland	ASTM D92	°C	154

Zastrzegamy sobie prawo do modyfikowania ogólnych charakterystyk naszych produktów, aby umożliwić naszym klientom czerpanie maksymalnych korzyści z najnowszych odkryć techniki.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

