

CHAMPION OEM SPECIFIC 5W30 C2/C3

This synthetic engine oil formulation guarantees a cleaner and better performing engine without lowering the oil drain interval. The broad applicability of this lubricant enables you to offer perfect maintenance to different vehicles of several major brands.

APPLICATIONS

This engine oil can be used in systems with or without exhaust gas aftertreatment where C2 or C3 engine oils are required. Furthermore, this engine oil has the Renault RN 17 specification level. This means that you can use this lubricant where RN0700 & RN0710 were previously required, enabling you to service several Dacia and Renault models with this engine oil.

FEATURES

Broad coverage: reduced lubricant costs

Significant friction reduction: improved fuel efficiency and lowered emissions

Excellent engine cleanliness: outstanding engine protection during the entire oil drain interval

PERFORMANCE

ACEA	C2	MB	226.52
ACEA	C3	MB	229.31
API	SN	MB	229.51
BMW	approval LONGLIFE-04	MB	approval 229.52
FIAT	9.55535-S1	OPEL	approval 0V 040 1547 - D30
FIAT	9.55535-S3	OPEL	GM-LL-A-025
FORD	WSS-M2C917-A	OPEL	GM-LL-B-025
GM	approval dexos2™	RENAULT	RN17 Level
HYUNDAI	.	VW	approval 505 00
IVECO	18-1811 Classe SC1	VW	approval 505 01
KIA	.		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.852
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	70.9
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	12.0
Viscosity index	ASTM D2270		167
B.N. [HClO4 method]	ASTM D2896	mg KOH/g	7.8
Pour point	ASTM D6892	°C	-45
Sulfated Ash	ASTM D874	Mass %	0.78

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

www.championlubes.com

