

MULTIGRADE SAE 0W20 C5 RFE

11/08/2023
65635

This synthetic low SAPS ACEA C5 lubricant meets the new fuel economy specification RN17 FE of Renault. The very low viscosity grade SAE 0W20 enables the engine to run at very high fuel-efficiency. This engine oil optimizes wear protection and engine cleanliness.

APPLICATIONS

This engine oil is especially formulated for use in the newest Renault diesel engines with DPF which require an oil according to the new fuel economy specification RN17 FE of Renault, which is only suitable for engines adapted for the purpose of lower fuel consumption. Furthermore it can be used in all engines requiring the new ACEA low SAPS specification C5, which has more fuel economy potential than ACEA C3.

FEATURES

Fuel economy: superior fuel economy and CO2 reduction.

Superb shear stability performance: optimal contribution to high temperature viscosity

Cold start: excellent low temperature performance

PERFORMANCE

ACEA

C5

RENAULT

RN17 FE

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.840
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	38.5
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	8.2
Viscosity index	ASTM D2270		195
B.N. (HClO ₄ method)	ASTM D2896	mg KOH/g	7.8
Pour point	ASTM D6892	°C	-48
Sulfated Ash	ASTM D874	Mass %	0.79

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolfoil.com

WOLFOIL
CORPORATION