WOLF VITALTECH 5W40

25/09/2026
16116

This is a full synthetic lubricant based on carefully selected very high quality base oils and additives of the latest generation, specially designed to meet the strict requirements of manufacturers. These provide an excellent fluidity at low temperatures, a very low resistance when starting, an exceptional viscosity index and a very high thermal stability.

APPLICATIONS

This oil is used in gasoline engines of cars, which meet the highest performance, and diesel engines of passenger cars with turbo and direct fuel injection. The high quality allows extended drain intervals, according to the specific requirements of manufacturers.

FEATURES

Engine protection: high level of engine cleanliness and durability
Cold start: high level of fluidity at low temperature
Enhanced drain interval: the purpose is a long drain interval

SPECIFICATIONS

ACEA	A3/B3-16
ACEA	A3/B4
API	approval SN Plus
API	approval SP
API	CF
API	SN
BMW	LONGLIFE-01
CHRYSLER	MS 12991
FIAT	9.55535-H2
FIAT	9.55535-M2
FIAT	9.55535-Z2
MB	226.5
MB	approval 229.3
OPEL	GM-LL-A-025
OPEL	GM-LL-B-025
PORSCHE	approval A40
PSA	B71 2296
RENAULT	RN 0700
RENAULT	RN 0710
VW	approval 502 00
VW	approval 505 00

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.858
Kinematic viscosity at 40°C	ASTM D445	mm^2/s	86.0
Kinematic viscosity at 100°C	ASTM D445	mm^2/s	14.4
Viscosity index	ASTM D2270		175
B.N. (HCLO4 method)	ASTM D2896	mg KOH/g	10.5
Pour point	ASTM D6892	°C	-45
CCS viscosity at -30°C	ASTM D5293	mPa.s	6100
Sulfated Ash	ASTM D874	Mass %	1.27
Flash Point COC	ASTM D92	°C	220

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com