

WOLF AGRIFLOW BIOCHAIN

14/04/2025
5503

Quickly biodegradable product, which is composed of vegetable oils and toxicologically neutral components, which are absorbed by micro-organisms in the shortest possible time. It presents an exceptional viscosity/temperature relation and a very good stability at low temperatures. It has a remarkable adhesive power for this type of product.

KÄYTTÖKOhteet

This product is mainly used as a biodegradable lubricant for chain saws.

OMINAISUUDET

Biodegradability: vegetable oil, quick decomposition
Stickiness: strong adhesive power

LUOKITUKSET

ISO 68 CEC L-33-T-82

TYYPILLISET OMINAISUUDET

Testi	Menetelmä	Yksikkö	Keskimääräinen tulos
Tiheys lämpötilassa 15 °C	ASTM D4052	g/ml	0.912
Kinemaattinen viskositeetti lämpötilassa 40 °C	ASTM D445	mm ² /s	69
Kinemaattinen viskositeetti lämpötilassa 100 °C	ASTM D445	mm ² /s	13.6
Viskositeetti-indeksi	ASTM D2270		204
Jähmepiste	ASTM D6892	°C	-21
Leimahduspiste (COC)	ASTM D92	°C	>200
Väri	VISUAL		GREEN
Biodegradability	CEC L-33-T-82	%	>90

Pidätämme oikeuden muuttaa tuotteidemme yleisominaisuuksia, jotta asiakkaamme voivat hyödyntää uusimpia teknisiä uudistuksiamme.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com

