

CHAMPION COMPETE

SN C2/C3 5W30

This full synthetic engine oil is designed to meet the core requirements of ACEA and API for passenger cars. It offers complete protection of both the aftertreatment system and the engine, regardless the driving conditions. This product may not be available in your region. Please, consult your local sales contact for more information.

APPLICATIONS

Formulated to meet recent OEM specifications. It can be used to service a wide range of EURO 4 and EURO 5-engines of different manufacturers, with or without diesel particulate filter.

FEATURES

Broad coverage: reduced lubricant costs.

Significant friction reduction: improved fuel efficiency and lowered emissions.

PERFORMANCE

| | | | |
|-------------|-----------|------------|---------------|
| ACEA | C2 | API | SN/CF |
| ACEA | C3 | MB | 229.31 |

TYPICAL CHARACTERISTICS

| Test | Method | Unit | Average results |
|------------------------------|------------|--------------------|-----------------|
| Density at 15°C | ASTM D4052 | g/ml | 0.850 |
| Kinematic viscosity at 40°C | ASTM D445 | mm ² /s | 68.0 |
| Kinematic viscosity at 100°C | ASTM D445 | mm ² /s | 11.8 |
| Viscosity index | ASTM D2270 | | 171 |
| B.N. (HClO4 method) | ASTM D2896 | mg KOH/g | 6.8 |
| Pour point | ASTM D6892 | °C | -39 |
| Sulfated Ash | ASTM D874 | Mass % | 0.78 |
| Flash Point COC | ASTM D92 | °C | 230 |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

