

CHAMPION AGRILINE 4T SAE 30 SJ

This is an engine oil specifically designed for the lubrication of modern 4-stroke gasoline engines. The special composition ensures a perfect operation of the equipment and an excellent protection against dirt and deposits.

APPLICATIONS

It is specifically formulated for the lubrication of the 4-stroke engines of garden and construction machines lawn mowers and auxiliary engines.

FEATURES

Total engine protection: good engine protection and cleanliness

PERFORMANCE

API

SJ/CD

JASO

MA

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.888
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	100
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	11.4
Viscosity index	ASTM D2270		99
B.N. [HClO ₄ method]	ASTM D2896	mg KOH/g	6.0
Pour point	ASTM D6892	°C	-27
Flash Point COC	ASTM D92	°C	235

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

