

# WOLF AROWEP ISO 100

14/04/2025  
4108

This is an extreme pressure oil for industrial gears. The paraffinic character of the base oil ensures an excellent course of the viscosity/temperature curve and a high resistance against oxidation and ageing. The favorable property of mineral base oil is further strengthened by the addition of appropriate additives. The high pressure additives based on sulfur and phosphorus compounds form a chemical film on tooth surfaces and as such prevents wear and a noticeable reduction in friction. Special anti-corrosion and anti-foam additives complete the composition of this oil.

## APPLICATIONS

It is recommended for the lubrication of gearboxes (lubrication by oil bath, oil mist or oil circulation) and it is specifically suitable for heavy loads and high temperature.

## FEATURES

Extreme pressure properties: superior EP properties  
Anti-wear and oxidation stability: adequate protection of systems

## SPECIFICATIONS

AGMA	9005-E02	ISO	100
AISE	224	DAVID BROWN	S1.53.101E
DIN	51517 CLP		

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.885
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	94
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	10.6
Viscosity index	ASTM D2270		95
A.N. (Colorimetric)	ASTM D974	mg KOH/g	0.34
Pour point	ASTM D6892	°C	-24
Flash Point COC	ASTM D92	°C	235

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.