

WOLF VITALTECH MULTI VEHICLE ATF

25/08/2023
3010

This is a full synthetic lubricant based on carefully selected very highly refined base oils for automatic transmissions, meeting the requirements of most American, Japanese and European manufacturers.

APPLICATIONS

Its versatile nature guarantees it can be used in automatic transmissions and torque converters for most passenger cars, off-road vehicles and SUVs.

FEATURES

Frictional properties: very smooth gear shifting, no vibration
Anti-wear protection: significantly extended transmission life
Extended oil life: excellent thermal and oxidation stability

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com



PERFORMANCE

JASO	M315, Class 1A	HYUNDAI	SP-II
AISIN-WARNER	JWS 3309	HYUNDAI	SP-III
AISIN-WARNER	JWS 3314	JAGUAR	JLM 20292 (LA 3403-M115)
AISIN-WARNER	JWS 3317	JAGUAR	JLM 21044
ALFA ROMEO	HP20	LAND ROVER	LR002748
ALLISON	C4	LAND ROVER	N402
ALLISON	TES 295	MAZDA	ATF F-1
ALLISON	TES 389	MAZDA	MV TYPE M5
BMW	81 22 9 400 275	MB	236.10
BMW	81 22 9 401 220	MB	236.11
BMW	83 22 0 026 922	MB	236.3
BMW	83 22 0 403 248	MB	236.5
BMW	83 22 0 403 249	MB	236.6
BMW	83 22 2 355 599	MB	236.7
BMW	83 22 9 407 765	MB	236.8
BMW	ATF 6	MB	236.9
BMW	ETL 7045E	MB	236.91
BMW	ETL 8072B	MB	4030401
BMW	LA 2634	MB	ATF J2
BMW	LT 71141	MB	DIA QUEEN ATF-PA
CHRYSLER	AS68RC ATF	MB	V5AWF
CHRYSLER	ATF +3 AND +4	MB	MATIC-D
CHRYSLER	MS 9602	MB	MATIC-J
DAIMLER TRUCK	DTFR 13C100	MB	MATIC-K
DAIMLER TRUCK	DTFR 13C110	MB	MATIC-W
DAIMLER TRUCK	DTFR 13C140	MB	LA 3403-M115
DAIMLER TRUCK	DTFR 13C150	MB	P/N Z 000169756
DAIMLER TRUCK	DTFR 13C170	MB	MATIC-D2
DAIMLER TRUCK	DTFR 13C180	MB	TYPE T
FIAT	9.55550-AV1	MB	TYPE T-III
FIAT	9.55550-AV4	MB	TYPE T-IV
FORD	MERCON	MB	VOLVO Constr. Equip. (VCE)
FORD	MERCON V	MB	1273,41
FORD	WSS-M2C195-A	MB	1161540
FORD	WSS-M2C919-E	MB	G 052 025
FORD	WSS-M2C922-A1	MB	G 052 055
GM	DEXRON II-D	MB	G 052 162
GM	DEXRON II-E	MB	G 052 533
GM	DEXRON III-G	MB	G 052 990
GM	DEXRON III-H	MB	G 055 025
HONDA	ATF Z-1	MB	G US 000 162
HYUNDAI	ATF RED 1K	MB	TE-ML 11A
		MB	TE-ML 11B

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com



TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.851
Kinematic viscosity at 40°C	ASTM D445	mm²/s	36.3
Kinematic viscosity at 100°C	ASTM D445	mm²/s	6.84
Viscosity index	ASTM D2270		150
Pour point	ASTM D6892	°C	-48
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	<=20000
Flash Point COC	ASTM D92	°C	218
Colour	VISUAL		RED

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

