29/04/2024 65607

WOLF OFFICIALTECH 5W30 C3

This is a full synthetic lubricant based on carefully selected very high quality base oils, formulated using the latest technology for Mid SAPS catalyst compatible engine oils. Its special formulation combines fuel economy with an extended service life. The reduced ash formulation protects particulate filters and exhaust aftertreatment devices.

APPLICATIONS

This dexos 2TM approved oil is required for all new GM/Opel/Vauxhall/Chevrolet diesel and gasoline models. GM/Opel has advised that the dexos 2TM specification is backward compatible to older GM/Opel specifications (GM-LL-A-025 and GM-B-LL-025). The majority of GM/Opel/Vauxhall/Chevrolet diesel and gasoline vehicles can use dexos 2TM lubricants. C2* meets all engine protection requirements of ACEA C2.

FEATURES

Aftertreatment protection: full aftertreatment device protection Total engine protection: outstanding engine cleanliness and durability Fuel economy: lower fuel consumption and CO2 emissions

SPECIFICATIONS

ACEA C2 ACEA C3 API CF

 BMW
 LONGLIFE-04

 CHRYSLER
 MS 11106

 FIAT
 9.55535-S3

 FORD
 WSS-M2C917-A

 GM
 approval dexos2™

229.31

HYUNDAI . KIA .

MB

 MB
 approval 229.51

 MB
 approval 229.52

 OPEL
 GM-LL-A-025

 OPEL
 GM-LL-B-025

 VW
 502 00

 VW
 505 00

 VW
 505 01



TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.850
Kinematic viscosity at 40°C	ASTM D445	mm²/s	67.1
Kinematic viscosity at 100°C	ASTM D445	mm²/s	12.2
Viscosity index	ASTM D2270		182
B.N. (HCLO4 method)	ASTM D2896	mg KOH/g	8.0
Pour point	ASTM D6892	°C	-39
CCS viscosity at -30°C	ASTM D5293	mPa.s	5400
Sulfated Ash	ASTM D874	Mass %	0.77
Flash Point COC	ASTM D92	°C	234

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

