

# GEAR OIL SAE GL 4 75W80 ZF

22/08/2023  
2202

*This is a full synthetic lubricant based on carefully selected very high quality base oils, which is recommended for the manual transmissions of most commercial vehicles. It is adapted to the requirements of synchromesh transmissions, procuring improved shift comfort, low temperature fluidity and longer service life.*

## APPLICATIONS

This product meets the requirements of many commercial vehicle builders and/or gearbox manufacturers, including DAF, IVECO, Eaton Europe (300.000 km or 3 years), Renault (in accordance with B0032/2 Annex 3) and Volvo.

## FEATURES

Frictional properties: very smooth shift performance  
Anti-wear protection: significantly extended transmission life  
Extended oil life: excellent thermal and oxidation stability

## PERFORMANCE

API	GL-4	VOLVO	97305
DAF	MEET REQUIREMENTS	VOLVO	97307
DAIMLER TRUCK	DTFR 13B150	ZF	TE-ML 01L
EATON	Extended drain	ZF	TE-ML 02L
IVECO	MEET REQUIREMENTS	ZF	TE-ML 08
MAN	341 E-3	ZF	TE-ML 13
MAN	341 Z-4	ZF	TE-ML 16K
MB	235.4	ZF	TE-ML 24A
RENAULT	B0032/2 Annex 3		

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.856
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	54.6
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	9.43
Viscosity index	ASTM D2270		157
Pour point	ASTM D6892	°C	-42
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	80000
Flash Point COC	ASTM D92	°C	234

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolfoil.com](http://www.wolfoil.com)

**WOLFOIL**  
CORPORATION