

RADIATOR COOLANT 50/50

11/08/2023
5069

This is an anti-freeze solution, based on mono-ethylene glycol and anti-corrosion additives in demineralised water. It contains no nitrites, amines or phosphates and gives excellent protection against corrosion without deposit formation. Easy to apply, the solution is already prepared.

APPLICATIONS

This liquid can be used in cooling circuits of the open or closed type with a protection against freezing until -36°C. Can be used during the whole year.

FEATURES

Anti-corrosion properties: complete system protection

Easy to use: ready-mixed

PERFORMANCE

ASTM	D3306	FIAT	55523/1
ASTM	D4985	FORD	SSM-97B9102A
BS	6580-1992	GME	13368
SAE	J1034	MAN	324
BMW	N600.69.0	SCANIA	S28917.3
DAVID BROWN	DBL-7700	VW	TL-VW774

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
pH	ASTM D1287		7.7
Density at 20°C	ASTM D4052	g/ml	1.073
Colour	VISUAL		Blue
Freezing point (refracto)	ASTM D3321	°C	-36
Water content	ASTM D1123	% wt/wt	50.0

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolfoil.com

WOLFOIL
CORPORATION