

CHAMPION HYDRO HLP-D ISO 32

This is a mineral oil-based hydraulic fluid containing a selective additive system, for protection of hydraulic systems, plus the addition of detergent/dispersant additives. It meets the HLPD requirements.

APPLICATIONS

This oil is suited for use in hydraulic systems, where due to high ingresses of water or contamination a high level of dispersancy is required to prevent water dropout in the system.

FEATURES

Anti-wear and oxidation stability: superior protection.

: excellent anti-foam properties.

Temperature stability: adequate viscosity stability.

PERFORMANCE

DIN 51524 T2 HLPD **MAN** N698-H-LPD

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.875
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	33.34
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	5.865
Viscosity index	ASTM D2270		120
Pour point	ASTM D6892	°C	-30
Flash Point COC	ASTM D92	°C	210

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

