

WOLF ESSENTIAL

CI-4/SL 15W40

11/08/2023
75702

This engine oil meets the prime requirements of ACEA and API for heavy-duty engines. It combines wear reducing- and cleaning properties into one lubricant.

APPLICATIONS

Suitable for all modern Euro II, III and some Euro IV diesel engines of heavy-duty equipment, making it a great lubricant for mixed fleet maintenance.

FEATURES

Engine protection: outstanding engine cleanliness and durability

PERFORMANCE

| | | | |
|------|------------------|-----|-------|
| ACEA | A3/B4 | API | CH-4 |
| ACEA | E7 | MB | 228.3 |
| API | approval CI-4/SL | MB | 229.1 |
| API | CG-4 | | |

TYPICAL CHARACTERISTICS

| Test | Method | Unit | Average results |
|---------------------------------|------------|--------------------|-----------------|
| Density at 15°C | ASTM D4052 | g/ml | 0.882 |
| Kinematic viscosity at 40°C | ASTM D445 | mm ² /s | 95.7 |
| Kinematic viscosity at 100°C | ASTM D445 | mm ² /s | 13.7 |
| Viscosity index | ASTM D2270 | | 145 |
| B.N. (HClO ₄ method) | ASTM D2896 | mg KOH/g | 8 |
| Pour point | ASTM D6892 | °C | -33 |
| Flash Point COC | ASTM D92 | °C | 225 |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com

