

WOLF AGRIFLOW 4T 15W40

14/04/2025
1406

This engine oil is specifically adapted for the lubrication of modern 4-stroke gasoline engines. The special composition ensures a perfect operation of the equipment and an excellent protection against dirt and deposits.

APPLICATIONS

It is specifically formulated for the lubrication of the 4-stroke engines of garden and construction machines, lawn mowers and auxiliary engines, Through its multigrade character, it can be used all year round.

FEATURES

Total engine protection: performance in keeping the engine clean

SPECIFICATIONS

ACEA	A3/B4-98	API	CF-4
ACEA	E2-level	API	SJ
API	CF		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.881
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	100
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	14
Viscosity index	ASTM D2270		142
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	7.6
Pour point	ASTM D6892	°C	-33
CCS viscosity at -20°C	ASTM D5293	mPa.s	6850
Sulfated Ash	ASTM D874	Mass %	1.0
Flash Point COC	ASTM D92	°C	228

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com

